

SC0407E / SC0610E**CRAWLER SCISSOR LIFT**

LGMG's crawler scissor lift is easy to drive on slopes or uneven ground, and has excellent obstacle-surpassing performance, which is very suitable for the environment with low ground pressure. Compact in size with 360 degree turning on the spot, suitable for use in narrow spaces. Humanized design, simple operation and more convenient maintenance

**SPECIFICATIONS**

Models	SC0407E (SC1532E)		SC0610E (SC2240E)	
Measurements	Metric	Imperial	Metric	Imperial
Work Height Max.	6.5m	21'4"	8.8m	28'10"
A Platform Height-Raised	4.5m	14'9"	6.8m	22'4"
B Platform Length	1.29m	4'3"	1.9m	6'3"
C Platform Width	0.7m	2'4"	0.73m	2'5"
D Overall Length	1.47m	4'10"	2.05m	6'9"
E Overall Width	0.78m	2'7"	0.99m	3'3"
F Overall Height-Guardrails Up	1.99m	6'6"	2.19m	7'2"
G Extension Deck	0.6m	2'	0.9m	2'11"
H Wheelbase	0.95m	3'1"	1.55m	5'1"
Ground Clearance	118mm	5"	115mm	5"
Productivity				
Max. Platform Occupancy	1 (in) / 0 (out)		2 (in) / 0 (out)	
Platform Capacity	200kg	441 lbs	250kg	551 lbs
Platform Capacity-Extension Deck	115kg	254 lbs	120kg	265 lbs
Gradeability-Stowed	25%	25%	25%	25%
Min. Turning Radius	Turning on the spot		Turning on the spot	
Raise/Lower Speed	20s / 20s	20s / 20s	36s / 36s	36s / 36s
Power				
Power Source	24V 130Ah	24V 130Ah	24V 115Ah	24V 115Ah
Hydraulic System				
Hydraulic Oil Capacity	4L	1gal	5.5L	1.4gal
Weight				
Machine Weight (CE/ANSI)	800kg	1764 lbs	1600kg	3528 lbs

